APPLICATION UNDER UNITED STATES PATENT LAWS

Atty. Dkt. No. PW 0305111
<u>(M#)</u>

Invention: IMAGE PROCESSING METHOD

Inventor (s):   YAMAGUCHI, Takashi
                MIKI, Takeo

For correspondence Address

00909

Pillsbury Winthrop LLP

<u>This is a:</u>

☐ Provisional Application

☒ Regular Utility Application

☐ Continuing Application
   ☐ The contents of the parent are incorporated
      by reference

☐ PCT National Phase Application

☐ Design Application

☐ Reissue Application

☐ Plant Application

☐ Substitute Specification
   <u>Sub. Spec</u> Filed _____
          in App. No. _____/_____

☐ <u>Marked up Specification re</u>
   Sub. Spec. filed _____
          In App. No _____/_____

SPECIFICATION

TITLE OF THE INVENTION

IMAGE PROCESSING METHOD

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is based upon and claims the

5   benefit of priority from the prior Japanese Patent

Applications No. 2002-214414, filed July 23, 2002; and

No. 2003-118468, filed April 23, 2003, the entire

contents of both of which are incorporated herein by

reference.

10   BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an image

processing apparatus which creates composite image

information by embedding, in visible main image

15   information (e.g., a human facial image), another

additional sub-information (e.g., security information)

in an invisible state, and restores the embedded

sub-information from the recorded composite image

information, and a printed material on which the

20   composite image information created by the image

processing apparatus is printed.

2. Description of the Related Art

Recently, with the trend toward computerization of

information and the proliferation of the Internet,

25   increasing importance has been attached to an

electronic watermarking technique, digital signature

technique, and the like to prevent counterfeiting and

alteration of images. The above electronic watermarking technique is a technique of embedding additional sub-information (sub-image information) in main image information in an invisible state. For example, the electronic watermarking technique is used for a personal authentication medium such as an ID card on which personal information is recorded or a literary work. The electronic watermarking technique can prevent unauthorized copying, counterfeiting, and tampering of a personal authentication medium and literary work, thereby protecting the personal information on the personal authentication medium and the copyright of the literary work.

For example, Jpn. Pat. Appln. KOKAI Publication No. 9-248935 discloses en electronic watermarking technique of embedding data in image data output onto a printed material by using the characteristics of high spatial frequency components and color difference components which are difficult for man to perceive. Jpn. Pat. Appln. KOKAI Publication No. 2001-268346 discloses a printing apparatus for electronic watermarks that can be recognized through optical filters.

Recording apparatuses for recording composite image information created by the above electronic watermarking technique on a medium include, for example, a recording apparatus based on a

sublimation/thermal transfer recording scheme and a recording apparatus based on a fusion thermal transfer recording scheme.

In general, in the sublimation/thermal transfer recording scheme, materials that can be dyed with sublimable materials are limited. For this reason, the sublimation/thermal transfer recording scheme can be adapted to only limited recording media; the degree of freedom of choice regarding recording media on which images are recorded is low. According to the sublimation/thermal transfer recording scheme, therefore, materials that can be used as recording media are limited. This tends to degrade security. In addition, sublimable dyes generally have poor image durability, e.g., poor light resistance and poor solvent resistance.

In contrast to this, in the fusion thermal transfer recording scheme, a material having good light resistance can be generally selected as a coloring material. The fusion thermal transfer recording scheme therefore allows a high degree of freedom of choice regarding recording media. In the fusion thermal transfer recording scheme, therefore, a high-specialty recording medium can be used. This makes it possible to improve security. The fusion thermal transfer recording scheme, however, uses a dot area gradation method of performing gradation recording by changing

the sizes of transferred dots. With this scheme,
therefore, it is difficult to realize as high gradation
performance as that with the sublimation/thermal
transfer recording scheme.

5   In order to solve this problem, for example,
Jpn. Pat. Appln. KOKOKU Publication No. 6-59739
discloses a method of recording transferred dots in a
so-called staggered array (this method will be referred
to as an alternate driving/recording scheme

10   hereinafter).

As described above, the electronic watermarking
technique is applied not only to electronic information
but also to printed materials such as driver's
licenses, credit cards, and membership cards. For

15   example, Jpn. Pat. Appln. KOKAI Publication
No. 2001-274971 discloses an electronic watermarking
technique of printing an image upon embedding a given
image therein. According to this technique, the
embedded image is difficult for man to perceive, and

20   can be restored even after the image is printed.

A technique is also disclosed in Japanese Patent
No. 2840825, in which a hologram film is formed on a
personal authentication medium such as a driver's
license, credit card, or membership card to prevent

25   copying thereof.

In another known technique, security is improved
by, for example, printing a facial image (to be

referred to as a ghost image hereinafter) lower in density than a normal facial image on a side of the normal facial image.

BRIEF SUMMARY OF THE INVENTION

5   It is an object of the present invention to provide an image processing method and apparatus which create a medium with high security on which an image obtained by embedding sub-information in main image information such as a facial image or a ghost image

10   created from a facial image is recorded, a printed material, and a printing method.

According to the present invention, there is provided an image processing method of creating composite image information by embedding

15   sub-information in main image information, comprising performing, for the main image information, first pre-processing corresponding to pixel formation processing for image recording, performing second pre-processing as geometric transformation processing

20   for the main image information having undergone the first pre-processing, performing embedding processing of creating composite image information by embedding sub-information in the main image information, and performing transformation processing inverse to the

25   transformation processing in the second pre-processing for the composite image information created by the embedding processing.

According to the present invention, there is provided an image processing method of recording, on a recording medium in a visible state, composite image information created by embedding sub-information in visible main image information in an invisible state, comprising performing, for the main image information, first pre-processing corresponding to pixel formation processing for image recording, performing second pre-processing as geometric transformation processing for the main image information having undergone the first pre-processing, performing embedding processing of creating composite image information by embedding sub-information in the main image information having undergone the second pre-processing in an invisible state, performing transformation processing inverse to the transformation processing in the second pre-processing for the composite image information created by the embedding processing, and recording, on a recording medium, the composite image information, inversely transformed by the inverse transformation processing, by performing an alternate driving/ recording scheme of alternately recording even-numbered and odd-numbered pixels in a main scanning direction of a recording device on a recording line basis.

According to the present invention, there is provided an image processing method of recording, on a recording medium in a visible state, composite image

information created by embedding sub-information in
visible main image information in an invisible state,
comprising performing first pre-processing of thinning
out main image information in correspondence with pixel

5   formation processing at the time of image recording,
performing second pre-processing including geometric
transformation processing of, after rotating the main
image information through a predetermined angle,
removing a thinned-out portion from the main image

10   information, compressing an effective portion of the
main image information, and reconstructing the main
image information, performing embedding processing of
embedding the sub-information in the main image
information having undergone the second pre-processing

15   in an invisible state by performing color difference
modulation processing using the main image information,
the sub-information, and key information used to
restore the sub-information, thereby creating composite
image information, performing inverse transformation

20   processing of performing transformation processing
inverse to transformation processing in the second
pre-processing for the composite image information
after expanding and reconstructing an effective portion
of the composite image information by inserting, in the

25   composite image information, not-to-be-recorded
information corresponding to the thinned-out portion of
the main image information, and performing recording

processing of recording, on a recording medium, the
composite image information, inversely transformed by
the inverse transformation processing, by performing an
alternate driving/recording scheme of alternately
recording even-numbered and odd-numbered pixels in a
main scanning direction of a recording device on a
recording line basis.

According to the present invention, there is
provided an image processing method of recording, on a
recording medium in a visible state, composite image
information created by embedding sub-information in
visible main image information in an invisible state,
comprising performing first pre-processing of thinning
out main image information in correspondence with pixel
formation processing at the time of image recording,
performing second pre-processing including geometric
transformation processing of, after rotating the main
image information through a predetermined angle,
removing a thinned-out portion from the main image
information, compressing an effective portion of the
main image information, and reconstructing the main
image information, performing embedding processing of
embedding the sub-information in the main image
information in an invisible state by superimposing the
main image information and superimposition information
created by performing color difference modulation
processing using the sub-information and key

information used to restore the sub-information, thereby creating composite image information, performing inverse transformation processing of performing transformation processing inverse to transformation processing in the second pre-processing for the composite image information after expanding and reconstructing an effective portion of the composite image information by inserting, in the composite image information, not-to-be-recorded information corresponding to the thinned-out portion of the main image information, and performing recording processing of recording, on a recording medium, the composite image information, inversely transformed by the inverse transformation processing, by performing an alternate driving/recording scheme of alternately recording even-numbered and odd-numbered pixels in a main scanning direction of a recording device on a recording line basis.

According to the present invention, there is provided an image recording apparatus comprising an embedding processing section which embeds sub-information in main image information in an invisible state by performing color difference modulation, thereby creating composite image information, an image processing section which performs pixel formation processing in the image recording apparatus for the composite image information created

by the embedding processing section, and performs

predetermined image processing in accordance with

recording operation, and a recording section which

records the composite image information processed by

5 the image processing section on a recording medium by

an alternate driving/recording scheme of alternately

forming even-numbered and odd-numbered pixels in a main

scanning direction of a recording device on a recording

line basis.

10 According to the present invention, there is

provided an image recording apparatus comprising a

first pre-processing section which thins out main image

information in correspondence with pixel formation

processing in the image recording apparatus, a second

15 pre-processing section which performs second

pre-processing including geometric transformation

processing of, after rotating the main image

information through a predetermined angle, removing a

thinned-out portion from the main image information,

20 compressing an effective portion of the main image

information, and reconstructing the main image

information, an embedding processing section which

embeds the sub-information in the main image informa-

tion in an invisible state by performing color

25 difference modulation processing, thereby creating

composite image information, an inverse transformation

processing which performs inverse transformation

processing of performing transformation processing inverse to transformation processing in the second pre-processing for the composite image information after expanding and reconstructing an effective portion

5   of the composite image information by inserting, in the composite image information, not-to-be-recorded information corresponding to the thinned-out portion of the main image information, and a recording section which performs recording processing of recording, on a

10   recording medium, the composite image information, inversely transformed by the inverse transformation processing section, by performing an alternate driving/recording scheme of alternately recording even-numbered and odd-numbered pixels in a main

15   scanning direction of a recording device on a recording line basis.

According to the present invention, there is provided an image recording apparatus comprising an embedding processing section which embeds

20   sub-information in main image information in an invisible state by performing color difference modulation, thereby creating composite image information, an image processing section which doubles the number of pixels of the composite image information

25   created by the embedding processing section in a sub-scanning direction of a recording device, and performing thinning-out processing in correspondence

with pixel formation processing in the image recording

apparatus, and a recording section which records the

composite image information processed by the image

processing section on a recording medium by using an

5   alternate driving/recording scheme of alternately

forming odd-numbered and even-numbered pixels in a main

scanning direction of the recording device on a

recording line basis and conveying the recording medium

with a convey pitch 1/2 a pixel pitch in the main

10   scanning direction.

According to the present invention, there is

provided a printed material on which a facial image as

a multilevel image, a ghost image as a facial image

obtained by reducing a density of the facial image, and

15   a binary image as a character are printed, wherein the

ghost image is printed while binary image data obtained

by performing predetermined processing for binary image

data associated with an image to be printed on the

printed material is embedded in the ghost image.

20   According to the present invention, there is

provided a printing method of printing a facial image

as a multilevel image, a ghost image as a facial image

obtained by reducing a density of the facial image, and

a binary image as a character on a printing medium,

25   wherein the image data printed as the ghost image is

created by performing predetermined processing for

binary image data associated with an image to be

printed on the printing medium and embedding the binary

image data having undergone the predetermined

processing in image data of the ghost image.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

5   FIG. 1 is a flow chart showing the overall flow of

processing in an image processing method according to

the first embodiment of the present invention;

FIG. 2 is a plan view schematically showing an

example of a created personal authentication medium;

10   FIG. 3 is a view for explaining image

interconnection to be recorded and recorded dots;

FIG. 4 is a view for explaining image

interconnection to be recorded and recorded dots;

FIG. 5 is a view for explaining the concept of the

15   first pre-processing;

FIG. 6 is a view for explaining the concept of the

second pre-processing;

FIG. 7 is a view for explaining a specific example

of the pixel array of image data;

20   FIG. 8 is a view for explaining a specific example

of the first pre-processing for the image data in

FIG. 7;

FIG. 9 is a view for explaining a specific example

of rotation processing in the second pre-processing for

25   the image data in FIG. 8;

FIG. 10 is a view for explaining a specific

example of compression processing in the second

pre-processing for the image data in FIG. 10;

FIG. 11 is a view showing the overall flow of electronic watermark embedding processing;

FIG. 12 is a flow chart schematically showing a procedure for electronic watermark embedding processing;

FIG. 13 is a flow chart schematically showing a procedure for electronic watermark embedding processing which prevents an overflow and underflow;

FIG. 14 is a graph for explaining an example of electronic watermark embedding processing;

FIG. 15 is a graph for explaining the first example of electronic watermark embedding processing which prevents an overflow and underflow;

FIG. 16 is a graph for explaining the second example of electronic watermark embedding processing which prevents an overflow and underflow;

FIG. 17 is a flow chart for explaining the flow of restoration processing of sub-information;

FIG. 18 is a block diagram schematically showing the arrangement of an image recording apparatus;

FIG. 19 is a block diagram schematically showing another arrangement of the image recording apparatus;

FIG. 20 is a view showing how dots recorded by the image recording apparatus are arrayed;

FIG. 21 is a view showing how dots recorded by an image recording apparatus according to the second

embodiment of the present invention are arrayed;

FIG. 22 is a flow chart for explaining the flow of actual processing according to the second embodiment;

FIG. 23 is a view schematically showing the arrangement of a printed material according to the third embodiment;

FIG. 24 is a flow chart showing processing sequences for printing a facial image and ghost image according to the third embodiment;

FIG. 25 is a view showing an example of the arrangement of the heating elements of the thermal head of a printer;

FIG. 26 is a schematic view showing a temperature distribution in the ink layer of a thermal transfer ink ribbon when the heating elements of the thermal head are simultaneously driven;

FIG. 27 is a schematic view showing a temperature distribution in the ink layer of the thermal transfer ink ribbon when the heating elements of the thermal head are alternately driven;

FIG. 28 is a view schematically showing the arrangement of a printed material according to the fourth embodiment;

FIG. 29 is a flow chart showing processing sequences for printing a facial image and ghost image according to the fourth embodiment;

FIG. 30 is a view for explaining diffusion

coefficients for error diffusion;

FIG. 31 is a flow chart showing an example of pixel data when quantization processing and error diffusion processing are performed;

FIG. 32 is a flow chart schematically showing a flow of processing in an image processing method; and

FIG. 33 is a flow chart showing processing sequences for printing a facial image and ghost image according to the fifth embodiment.

DETAILED DESCRIPTION OF THE INVENTION

Each embodiment of the present invention will be described with reference to the several views of the accompanying drawing.

The first embodiment will be described first.

FIG. 1 is a flow chart showing the overall flow of image processing by an image recording apparatus according to the first embodiment. The operation example shown in FIG. 1 exemplifies, as the first embodiment, the flow of processing for a personal authentication facial image to be printed on a personal authentication medium such as an ID card by the above image recording apparatus.

First of all, the above image recording apparatus performs image input processing of inputting a facial image as main image information (step S101). In this image input processing, a facial image of the holder of a personal authentication medium is photographed by a

camera. The resultant facial image information of the individual is then input as digital data. In the above image input processing, the facial image information of the individual may be input as digital data by

5 capturing a facial portrait using an image input unit such as a scanner.

When the facial image is input by the above image input processing, the above image recording apparatus performs the first pre-processing for the input facial

10 image (to be also referred to as main image information hereinafter) (step S102). In the first pre-processing, for example, thinning-out processing is performed for the facial image information input in the image input processing in step S101. With this operation, main

15 image information having undergone the first pre-processing, corresponding to the pixel formation processing by the image recording apparatus, is created.

The above image recording apparatus then performs

20 the second pre-processing (step S103). In the second pre-processing, image information subjected to embedding is created by geometric transformation processing. In the second pre-processing, for example, rotation processing is performed for the main image

25 information processed in the first pre-processing, and pixel portions thinned out in the first pre-processing are removed to compress the effective image size.

When image information subjected to embedding
(main image information having undergone all the
pre-processing) is created by the first pre-processing
and second pre-processing, the image recording
apparatus performs electronic watermark embedding
processing for the image information subjected to
embedding (step S104). In this electronic watermark
embedding processing, composite image information is
created by embedding, in image information subjected to
embedding, sub-information (sub-image information) in
an invisible state in which the information cannot be
perceived by the human eye.

When composite image information is created by the
above electronic watermark embedding processing, the
image recording apparatus performs post-processing for
the composite image information (step S105). In this
post-processing, for example, reverse rotation
processing for the composite image information created
in step S104, and expands the effective image size.
With this post-processing, an image (to-be-recorded
image information) to be recorded on a recording medium
is created.

Finally, the image recording apparatus performs
recording processing of recording the to-be-recorded
image information created in step S105 on the recording
medium serving as a personal authentication medium
(step S106). In this recording processing, the

to-be-recorded image information created in step S105
is recorded on the recording medium serving as a
personal authentication medium by the alternate
driving/recording scheme of alternately forming
even-numbered and odd-numbered pixels in the main
scanning direction on a recording line basis by using a
recording device typified by a thermal head.

In this flow of processing, a personal
authentication medium is created, on which the image
obtained by embedding the sub-information in the main
image information is recorded.

FIG. 2 is a view showing a personal authentication
medium 201 such as an ID card created by the processing
shown in FIG. 1.

As shown in FIG. 2, a personal authentication
facial image 202 of the holder is recorded on the
personal authentication medium 201. The facial image
202 on the personal authentication medium 201 is the
image created and recorded by the processing described
with reference to FIG. 1. In addition, personal
management information 203 such as an identification
number (No.), name, date of birth, and expiration date
is recorded on the personal authentication medium 201.

The personal authentication medium shown in FIG. 2
uses the personal management information 203 as the
sub-information in the electronic watermark embedding
processing in step S104 shown in FIG. 1. Consequently,

the personal authentication facial image 202 of the
personal authentication medium 201 is associated with
the personal management information 203. This makes it
difficult to partly tamper or counterfeit the personal
authentication medium 201, resulting in an improvement
in security.

The alternate driving/recording scheme, and more
specifically, the fusion thermal transfer recording
scheme of recording dots in a staggered array will be
described next. In the fusion thermal transfer
recording scheme of forming an image based on the
presence/absence of dots, when a multi-tone image is to
be expressed, the apparent density is controlled by
performing area modulation processing of changing the
areas of dots. For this reason, in the fusion thermal
transfer recording scheme, it is required to accurately
modulate the sizes of dots. In order to meet this
requirement, the alternate driving/recording scheme is
preferably used as the above fusion thermal transfer
recording scheme.

The above alternate driving/recording scheme is
a scheme of alternately driving the odd-numbered
heating elements of the odd-numbered lines and the
even-numbered heating elements of the even-numbered
lines of the recording head (line thermal head) on a
recording line basis. Assume that image information to
be recorded on a recording medium is arranged in a

lattice pattern, as shown in FIG. 3. According to the above alternate driving/recording scheme, in actual recording operation, the image information arranged in the lattice pattern shown in FIG. 3 is recorded in a staggered pattern, as shown in FIG. 4. In the alternate driving/recording scheme, therefore, the even-numbered information of each odd-numbered line and the odd-numbered information of each even-numbered line of the image information to be recorded are omitted in actual recording operation.

In the above alternate driving/recording scheme, even if sub-information is embedded in image information (to be simply recorded) in an invisible state by using electronic watermark embedding processing, only the area 1/2 that of the original image information becomes effective, and the remaining information is omitted. This means that the electronic watermark in the image recorded on the recoding medium is destroyed or changed. In general, when information is omitted and an electronic watermark is destroyed in the above manner, it is very difficult to restore sub-information. This makes it impossible to maintain security.

In the first embodiment, therefore, in performing the electronic watermark embedding processing in step S104, the first pre-processing in step S102 and the second pre-processing in step S103 are performed. In

addition, after the electronic watermark embedding

processing in step S104, the post-processing in step

S105 is performed. This makes it possible to prevent

the electronic watermark in the image recorded on the

5   recording medium from being destroyed even when the

above alternate driving/recording scheme is used.

The first pre-processing and second pre-processing

will be described next.

In the first pre-processing (step S102), image

10   information corresponding to pixels to which no energy

is applied in the alternate driving/recording scheme is

thinned out. For example, FIG. 5 shows the overall

array of image information to be recorded. Referring

to FIG. 5, black portions 401 correspond to pixels to

15   be recorded (information not to be thinned out), and

white portions 402 correspond to pixels not to be

recorded (information to be thinned out).

In the second pre-processing (step S103),

geometric transformation processing is performed for

20   the array of the image information having undergone the

first pre-processing. In the second pre-processing,

for example, 45° rotation processing is performed, and

thinned-out information is removed, thereby compressing

the effective image information size. More

25   specifically, when the image information array shown in

FIG. 5 is rotated through 45°, the black portions 401

(information not to be thinned out) are aligned, as

shown in FIG. 6.   Therefore, by removing the white

portions 402 (portions to be thinned out) and

re-arraying the information, an array of only image

information free from the influence of the alternate

5   driving/recording scheme can be created.

The first pre-processing and second pre-processing

will be further described with reference to specific

examples shown in FIGS. 7 to 10.

FIG. 7 shows the array of image information to be

10   recorded.   In the image information shown in FIG. 7,

4 (rows) × 4 (columns) pixels aij (i = 1 to 4, j = 1 to

4) are arranged.   When the image information shown in

FIG. 7 is thinned out by the first pre-processing, the

even-numbered data of the odd-numbered lines (the

15   pixels at the intersections of the odd-numbered rows

and the even-numbered columns) and the odd-numbered

data of the even-numbered lines (the pixels at the

intersections of the even-numbered rows and the

odd-numbered columns) of the array of the image

20   information are thinned out.   As a result, the image

information shown in FIG. 7 is transformed into the

image information shown in FIG. 8.   More specifically,

in the first pre-processing, pixels a12, a14, a21, a23,

a32, a34, a41, and a43 (the array elements marked X in

25   FIG. 8) are deleted from the image information. shown

in FIG. 7.

When 45° rotation processing is performed as the

second pre-processing for the image information shown

in FIG. 8, the image information shown in FIG. 8 is

transformed into the image information shown in FIG. 9.

When the processing (compression processing as the

5   second pre-processing) of re-arraying effective pixel

elements is performed for the image information shown

in FIG. 9, the image information shown in FIG. 9 is

transformed into the image information shown in

FIG. 10. That is, when the portions marked X in FIG. 9

10   are removed and the remaining pixels (effective image

information elements) are re-arrayed, image information

is obtained, in which pixels a11, a131, a22, a13, a41,

a33, a24, and a44 are arrayed, as shown in FIG. 10.

Note that in the case of the image information shown in

15   FIG. 10, information ("0" in this case) is stored,

which indicates that no information is recorded on

array elements as empty spaces.

When the image information shown in FIG. 7 is

compared with the image information shown in FIG. 10,

20   the actually recorded image information or the array

size of image information free from the influence of

the alternate driving/recording scheme is reduced (the

thick frame portion in FIG. 10). That is, when

electronic watermark embedding processing is so

25   performed as to make sub-information fall within the

thick frame portion in FIG. 10, the sub-information can

be recorded on a recording medium while being

completely held, even in the alternate driving/ recording scheme.

Note that post-processing (step S106) is processing totally reverse to the above processing.

In addition, a recording scheme other than the fusion thermal transfer recording scheme can be applied to image processing in this embodiment as long as gradation (tone) expression is realized by dot area modulation of to-be-recorded pixels.

FIG. 11 schematically shows a sequence for the above processing by the image recording apparatus.

Referring to FIG. 11, assume that main image information 601 is, for example, facial image information for personal authentication. In addition, sub-information 602 is information for improving the security of the main image information 601. For example, an image obtained by coding a name, date of birth, and the like or a graphic pattern such as a company logo is used as the sub-information 602. Referring to FIG. 11, assume that the sub-information 602 is "174". Key information 603 is information serving as a key for restoring the sub-information embedded in an invisible state by electronic watermark embedding processing.

First of all, the image recording apparatus creates image information 604 subjected to embedding by performing the first pre-processing and second

pre-processing for the main image information 601. The
image recording apparatus then performs electronic
watermark embedding processing 605 by using the image
information 604 subjected to embedding, sub-information
602, and key information 603 to create electronic
watermarked image information 606.

The image recording apparatus creates composite
image information 607 by performing post-processing for
the electronic watermarked image information 606 as
transformation processing inverse to the first
pre-processing and second pre-processing. Finally,
the image recording apparatus completes a personal
authentication medium 609 by executing recording
(printing) processing 608 of recording the composite
image information 607 on a recording medium.

The electronic watermark embedding processing 605
will be described in detail next.

The first embodiment can use a general electronic
watermark embedding technique, and is especially
compatible with an electronic watermark embedding
technique of performing electronic watermark embedding
by superimposing sub-information on main image
information.

Such electronic watermark embedding techniques are
disclosed in, for example, Jpn. Pat. Appln. KOKAI
Publication Nos. 11-168616 and 2001-268346. That is,
the electronic watermark embedding techniques disclosed

in, for example, Jpn. Pat. Appln. KOKAI Publication

Nos. 11-168616 and 2001-268346 can be applied to the

first embodiment. These electronic watermark embedding

techniques are described on the premise that main image

information is basically a color (full-color) image.

By applying, for example, the technique disclosed in

Jpn. Pat. Appln. KOKAI Publication No. 11-355554 to

these techniques, electronic watermark embedding

processing of embedding sub-information (sub-image

information) even in a monochrome image can also be

performed.

When it is required to determine the authenticity

of an image in which an electronic watermark is

embedded by the above electronic watermark embedding

technique, the sub-information recorded on the image in

an invisible state is restored by performing the

restoration processing described in the above

references and the like using key information.

FIG. 12 is a view showing the flow of electronic

watermark embedding processing using the color

difference modulation scheme described in

Jpn. Pat. Appln. KOKAI Publication No. 11-168616.

Application examples of the above color different

modulation scheme to the first embodiment will be

described below. The color difference modulation

scheme includes the following three features (1)

to (3):

(1) using the human visual characteristics;

(2) using a complementary color relationship, e.g., red + cyan = achromatic color (white) (in the case of additive color mixture); and

(3) applying a complementary color relationship and color different information (color difference modulation processing) to a high-frequency carrier pattern image.

By using the color difference modulation schemes described in cases (1) to (3), sub-information can be embedded in main image information in an invisible state.

In case (1) described above, as the frequency of an image increases, the gradation identification ability decreases, and color difference information becomes more difficult to discriminate than luminance information.

In case (2) described above, the additive color mixture of red and cyan (= green + blue) produces a complementary color relationship, so that when red and cyan are located side by side, they look achromatic, which is difficult to discriminate by the human eye.

In case (3) described above, red rich pixels and cyan rich pixels are repeatedly arranged by using a high-frequency carry pattern image. That is, this scheme utilizes the human visual characteristics that the small differences in color differences between

these pixels cannot be identified by the human eye, and
hence it is determined that the color difference amount
is plus or minus "0".

The composite image information (electronic
watermarked image) created by the above color
difference modulation scheme does not depend on any
image format, and hence can be expressed in any image
format. For example, the composite image information
(electronic watermarked image) created by the above
color difference modulation scheme can be expressed in
a new future image format as well as a currently
available image format such as BMP, TIFF, or JPEG.

The flow of electronic watermark embedding
processing in Jpn. Pat. Appln. KOKAI Publication
No. 11-168616 shown in FIG. 12 will be briefly
described below. For details, refer to the descriptive
contents of Jpn. Pat. Appln. KOKAI Publication
No. 11-168616.

Image information (main image information) 701
subjected to embedding is image information in which
to-be-embedded information is embedded. For example,
this information corresponds to a facial portrait
(facial image) of the holder of a personal authentica-
tion medium. The image information (main image
information) 701 subjected to embedding has, for
example, 24-bit information per pixel (eight bits for
each of R, G, and B).

A to-be-embedded image information
(sub-information) 702 is obtained by converting
information to be embedded into a binary image.
For example, this information corresponds to the
identification number of the personal authentication
medium. The to-be-embedded image information
(sub-information) 702 has 1-bit information per pixel.

Mask image information (key information) 703 is
image information used in image combining processing
and restoration (reproduction) of embedded image
information. For example, the mask image information
(key information) 703 has 1-bit information per pixel.

Smoothing processing 704 is performed with each
black pixel of the to-be-embedded image information 702
being converted into "1"; and each white pixel, "0".
For example, in the smoothing processing 704, a
(3 × 1)-pixel area including pixels on both ends of a
target pixel in the x direction is extracted, and the
weighted average of the extracted area is calculated.
In phase modulation processing 705, phase modulation is
performed for the mask image information 703 on the
basis of the smoothing processing result obtained by
the smoothing processing 704.

Color difference modulation processing 707 is
performed using a color difference amount ΔCd on the
basis of the phase modulation result obtained by the
phase modulation processing 705. In this color

difference modulation processing, for example, three

components, i.e., R (red), G (green), and B (blue), are

separately calculated. Composite image information 709

is created by performing superimposition processing 708

5   on the basis of the color difference modulation

processing result obtained by the color difference

modulation processing 707 and the image information 701

subjected to embedding.

As is also obvious from the above description,

10   the image information 701 subjected to embedding,

to-be-embedded image information 702, and mask image

information 703 in FIG. 12 are identical to the main

image information 601, sub-information 602, and key

information 603 in the first embodiment described with

15   reference to FIG. 11. The electronic watermark

embedding scheme shown in FIG. 12 can therefore be

applied to the first embodiment.

In the first embodiment, however, in order to

perform the first pre-processing and second

20   pre-processing for main image information in advance,

the array size of effective image information is

smaller than the original size of the main image

information as indicated by the thick frame in FIG. 10.

When, therefore, the composite image information 709 is

25   to be created by superimposing image information 701'

subject to embedding and superimposition image

information 710 obtained by color difference modulation

processing, as in the case of electronic watermark
embedding processing shown in FIG. 12, the effective
portion ("174" in this case) of the superimposition
image information 710 needs to completely fall within
5   the hatched portion of the image information 701'
subject to embedding.

    For example, the image information 701' subject to
embedding, superimposition image information 710, and
composite image information 709 are defined as follows:
10   image information subject to embedding:

$$SRC\_C(x, y) \qquad \ldots (A\text{-}1)$$

        superimposition image information:

$$STL\_C(x, y) \qquad \ldots (A\text{-}2)$$

        composite image information:

15
$$DES\_C(x, y) \qquad \ldots (A\text{-}3)$$

(where $\underline{x}$ and $\underline{y}$ are the coordinate values of each image,
and C = {R (red), G (green), B (blue)} plane. In
24-bit color computation, each value is an integral
value from 0 to 255.)
20   In such a case, the superimposition processing 708
is expressed by

$$DES\_R(x, y) = SRC\_R(x, y) + STL\_R(x, y) \quad \ldots (B\text{-}1)$$

$$DES\_G(x, y) = SRC\_G(x, y) + STL\_G(x, y) \quad \ldots (B\text{-}2)$$

$$DES\_B(x, y) = SRC\_B(x, y) + STL\_B(x, y) \quad \ldots (B\text{-}3)$$

25   In the first embodiment, R (red), G (green), and B
(blue) are used as fundamental colors for computation
based on the additive color mixture. However, using C

(cyan), M (magenta), and Y (yellow) as fundamental colors for computation based on the subtractive color mixture makes no substantial difference.

The electronic watermark embedding scheme in FIG. 12 uses a complementary color relationship as described above to perform color difference modulation processing. In this color difference modulation processing, the predetermined color difference amount ΔCd is used. In this case, an experimentally obtained difference amount (predetermined value) in luminance value between red and cyan is held as data.

The above superimposition image information 710 is created on the basis of the to-be-embedded image information 702, mask image information 703, and color difference amount ΔCd. In contrast to this, for the to-be-embedded image information 702, setting parameters are limited to a certain degree. This is because this information is often pertinent information for improving the security of the image information 701 subjected to embedding. The mask image information 703 serves as a key for restoring the to-be-embedded image information 702 when necessary, and hence setting parameters are limited to a certain degree. For this reason, the value of the color difference amount ΔCd plays an important role as a setting parameter for electronic watermark embedding processing.

The values of DES_R(x, y), DES_G(x, y), and

DES_B(x, y) are integers that fall within the range of 0 to 255 in the case of 24-bit color computation. For this reason, if the calculation result is "0" or less, the corresponding value is set to "0". If the

5   calculation result is "255" or more, the corresponding value is set to "255". If, however, the calculation result is smaller than "0", an underflow occurs. If the calculation result is larger than "255", an overflow occurs. In such a case, the color difference

10   balance is lost, and a complementary color relationship may not hold. In this case, the mask image information 703, which should have been embedded in an invisible state, may become visible and exposed. In the case shown in FIG. 12, since the color difference amount ΔCd

15   used for color difference modulation processing is a predetermined fixed value, an underflow or overflow does not easily occur.

The first correction method of preventing an overflow and underflow like those described above will

20   be described below.

In the first correction method, as shown in FIG. 13, before the color difference modulation processing 707 is performed in the processing in FIG. 12, color difference correction processing 711 for

25   correcting the color difference amount ΔCd on a pixel basis is executed in accordance with each pixel information of the image information 701 subjected to

embedding. That is, the color difference modulation processing 707 is performed by correcting the above color difference amount ΔCd to an appropriate value as well as using the predetermined color difference amount ΔCd. This makes it possible to prevent the occurrence of an underflow and overflow in the processing results obtained by the color difference modulation processing 707 and superimposition processing 708, thereby keeping the complementary color relationship.

The above color difference correction processing 711 is implemented by, for example, processes (1) to (4) described below:

(1) checking the distribution of the luminance information of each pixel of image information subjected to embedding;

(2) after color difference modulation processing of the color difference amount ΔCd (fixed value), obtaining pixels that will overflow or underflow upon superimposition processing on the basis of the information obtained in process (1) described above, thereby creating a table;

(3) performing first superimposition processing on the basis of the information of the table created in process (2) described above, and then calculating a color difference correction amount ΔCd-2, on a pixel basis, with which no overflow or underflow occurs; and

(4) performing color difference modulation

processing by using the color difference amount ΔCd
(fixed value) and the color difference correction
amount ΔCd-2 obtained in process (3) described above.

The second correction method of preventing an
overflow and underflow, which is different from the
above method, will be described next.

In the second correction method, the distribution
of the pixel luminance values of image information
subjected to embedding (created from main image
information) is compressed within a predetermined range
before sub-information is embedded in the image
information in electronic watermark embedding
processing.

In the case of 24-bit color computation, the
luminance value of each pixel takes an integral value
from 0 to 255. For this reason, when no compression
processing is done, the luminance value of an input
pixel and the luminance value of an output pixel have a
relationship represented by a function of a straight
line with a slope of "1", as shown in FIG. 14. That
is, FIG. 14 shows that there is no influence on the
luminance value of each pixel of the image information
subjected to embedding.

In contrast to this, FIG. 15 is a view showing the
relationship between the luminance value of an input
pixel and the luminance value of an output pixel when
the high-luminance and low-luminance portions of the

input pixels are respectively output as predetermined luminance values.

In the case shown in FIG. 15, each high-luminance input pixel (each pixel with a luminance value equal to or more than $255 - \Delta Cn1$) is output as a predetermined luminance value ($255 - \Delta Cn1H$), whereas each low-luminance input pixel (each pixel with a luminance value equal to or less than $\Delta Cn1L$) is output as a predetermined luminance value ($\Delta Cn1L$). According to the case shown in FIG. 15, of the luminance values of pixels to be output, low luminances (lower than $\Delta Cn1L$) and high luminances (higher than $255 - \Delta Cn1H$) are cut.

When electronic watermark embedding processing is performed after the luminance value of each pixel of image information subjected to embedding is compressed on the basis of the function shown in FIG. 15, the luminance value of each pixel of the image information subjected to embedding has a margin of $\Delta Cn1H$ on the high-luminance side, and a margin of $\Delta Cn1L$ on the low-luminance side. This makes it possible to prevent an overflow in the above superimposition processing within the range of $\Delta Cn1H$ on the high-luminance side, and an underflow in the superimposition processing within the range of $\Delta Cn1L$ on the low-luminance side.

When the luminance value of each pixel of image information subjected to embedding is compressed on the basis of the function shown in FIG. 15, high and low

luminance values are cut, but intermediate luminance values between them (luminances between high and low luminances) are output without any changes in the input values. For this reason, in a portion where the luminance values of input pixels are intermediate values, the tone of the image can be maintained. However, in portion where the luminance values of input pixels are high or low luminances, discontinuous luminance values appear.

In the case shown in FIG. 16, high-luminance portions of input pixels (areas with luminance values equal to or more than 255 - $\Delta Cn1H$) and low-luminance portions (areas with luminance vales equal to or less than $\Delta Cn1L$) are cut, and the luminance values are uniformly compressed and output. That is, FIG. 16 shows a function of a straight line connecting a point (255, 255 - $\Delta Cn1H$) at which the luminance value of an output pixel is set to 255 - $\Delta Cn1H$ when the luminance value of an input pixel is 255 and a point (0, $\Delta Cn1L$) at which the luminance value of an output pixel is set to $\Delta Cn1L$ when the luminance value of an input pixel is 0.

When electronic watermark embedding processing is performed after the luminance value of each pixel of image information subjected to embedding is compressed on the basis of the function shown in FIG. 16, the luminance value of each pixel of the image information

subjected to embedding has a margin of ΔCn1H on the

high-luminance side, and a margin of ΔCn1L on the

low-luminance side. This makes it possible to prevent

an overflow in the above superimposition processing

5   within the range of ΔCn1H on the high-luminance side

and an underflow in the superimposition processing

within the range of ΔCn1L on the low-luminance side.

When electronic watermark embedding processing is

performed after the luminance value of each pixel of

10   image information subjected to embedding is compressed

on the basis of the function shown in FIG. 16, all

the low-luminance portions, intermediate-luminance

portions, and high-luminance portions can be

continuously expressed in gradation.

15   If, however, the slope of a straight line like

the one shown in FIG. 16 is excessively changed, the

difference between the sub-information and the main

image information increases. This may produce a sense

of incongruity. In order to solve this problem, after

20   electronic watermark embedding processing is performed

upon compression of the luminance value of each pixel

of image information subjected to embedding on the

basis of the function shown in FIG. 16, the image

information may be processed by a function for

25   transformation inverse to that in FIG. 16. This makes

it possible to solve the above problem even if the

luminance value of each pixel of image information

subjected to embedding is compressed on the basis of the function shown in FIG. 16.

The compression processing of the luminance value of each pixel with respect to the above image information subjected to embedding can produce a better effect when it is used together with the color difference correction processing 711 in FIG. 13 described above.

A method of restoring sub-information when it is necessary to determine the authenticity of the image created by the image processing method described above will be described next.

In the first embodiment, after sub-information is embedded in main image information in an invisible state by electronic watermarking, key information is used to restore the sub-information from the recorded composite image information. As this key information, a binary (monochrome) image having a geometric pattern or the like is used. For example, this pattern includes a checkered pattern which is constituted by 2 × 3 pixels and has a period, and a pseudo-random pattern formed on a predetermined sheet.

The first restoration method will be described first.

The first restoration method is a restoration method of restoring (reproducing) sub-information by physically superimposing a restoration sheet on the composite image information recorded on a personal

authentication medium or the like. In this case, the sub-information can be visually checked by the naked eye. The restoration sheet is a transparent recording medium on which a graphic pattern for restoring the sub-information of a composite image is recorded. The graphic pattern for restoring the sub-information of the composite image is generated on the basis of key information. The graphic pattern recorded on the restoration sheet is formed as follows. First, only rotation processing in the second pre-processing (step S103) in FIG. 1 is performed for image information having the black pixels of key information as to-be-recoded information and the white pixels of the key information as not-to-be-recorded information. Thereafter, the even-numbered and odd-numbered pixels in the main scanning direction of a recording device are alternately recorded on a recording line basis in the same manner as in the recording processing (step S106) in FIG. 1 described above.

The second restoration method will be described next.

The second restoring method is a method of restoring sub-information by using a frequency filter. FIG. 17 is a flow chart for explaining the flow of the processing of restoring sub-information from a composite image recorded on a personal authentication medium and determining the authenticity of the

sub-information.

In the second restoration method, a restoration apparatus (authentication apparatus) for restoring sub-information from a composite image performs image input processing of inputting the composite image recorded (printed) on a personal authentication medium or the like (step S111). In this image input processing, an image input device such as a scanner or camera is used to read the composite image recoded on the personal authentication medium as digital data.

The above restoring apparatus then performs key information setting processing of setting information of the special frequency of key information corresponding to the composite image to be restored (step S112).

If, for example, there are a plurality of pieces of key information, key information to be used for the composite image recorded on each personal authentication medium is determined on the basis of information (e.g., identification information) associated with the personal authentication medium. That is, in the above key information setting processing, key information for the composite image recorded on a personal authentication medium is specified on the basis of information (e.g., identification information) associated with the personal authentication medium, and information of the

specific frequency of the key information is set.

If there is only one piece of key information, information of the specific frequency of the key information stored in the memory may be read out and set in the above key information setting processing. Assume that in this case, information of the specific frequency of the key information is held in the memory in the restoration apparatus in advance.

The restoration apparatus then performs electronic watermark restoration processing of restoring the sub-information embedded as an electronic watermark in the composite image (step S113). In this electronic watermark restoration processing, frequency filtering processing is performed for the composite image information input in the image input processing by using the specific frequency set in the above key information setting processing. For this frequency filtering processing, for example, FFT computation and a digital frequency filter can be used. With this electronic watermark restoration processing, sub-information is restored from the composite image recorded on the personal authentication medium.

Finally, the restoration apparatus performs authenticity determination processing of performing personal authentication (authenticity determination) on the basis of the processing result obtained by the above electronic watermark restoration processing (step

S114). In this authenticity determination processing,
it is determined whether or not the sub-information
restored by the processing in steps S111 to S113
described above is authentic. The determination result
obtained by this authenticity determination processing
is notified to the person who has made determination.

In using the second restoration method, if main
image information contains many frequency components
similar to the specific frequency component of key
information, the sub-information may not be accurately
restored, and authenticity determination may not be
accurately performed. The restoration precision of
sub-information can be improved by removing or
weakening frequency component of main image information
which are similar to the specific frequency component
of key information in advance.

If there are a plurality of pieces of key
information, key information having a frequency
component exhibiting little similarity to the frequency
components of main image information may be selected in
performing electronic watermark embedding processing.
This can improve the restoration precision of
sub-information restored from a composite image by
using the second restoration method.

An image recording apparatus using the above image
processing method will be described next.

FIGS. 18 and 19 schematically show the

arrangements of image recording apparatuses. The image

recording apparatus shown in FIG. 18 or 19 is

constituted by an image input section 121 serving as an

image input means, an electronic watermark embedding

5 section 122, an image processing section (color

conversion section) 123 for printing operation, a

recording signal conversion section 124, and a

recording section 125.

The image input section 121 serves to input image

10 information such as a facial image which is main image

information. The image input section 121 inputs

digital data as main image information by photographing

a facial image as main image information to be recorded

on a personal authentication medium or capturing a

15 facial portrait with an input device such as a scanner.

Assume that the image input section 121 inputs, for

example, main image information constituted by three

planes, i.e., R, G, and B planes.

The electronic watermark embedding section 122

20 performs the processing in steps S102 to S105 in

FIG. 1. That is, the electronic watermark embedding

section 122 performs the first pre-processing (step

S102), second pre-processing (step S103), electronic

watermark embedding processing (step S104), and

25 post-processing (step S105).

As described with reference to step S102, the

first pre-processing is thinning-out processing for

main image information. As described with reference to step S103, the second pre-processing is constituted by rotation processing for the main image information having undergone the first pre-processing and

5   compression processing for the main image information rotated by the rotation processing. As described with reference to step S104, the electronic watermark embedding processing is processing of embedding sub-information in the image information having

10   undergone the second pre-processing. As described with reference to step S105, the post-processing is constituted by reverse rotation processing of rotating the image information, in which the sub-information is embedded by the electronic watermark embedding

15   processing, in the reverse direction to that in the second pre-processing and expansion processing of expanding the image information having undergone the reverse rotation processing.

The image processing section (color conversion
20   section) 123 for printing operation converts received image information into image information for printing operation. For example, the image processing section 123 performs color conversion processing of color-converting pieces of R (red), G (green), and B
25   (blue) image information into pieces of C (cyan), M (magenta), and Y (yellow) image information. For example, in this color conversion processing, color

conversion is performed by using a 3 × 3 or 3 × 9 color conversion matrix in accordance with the recording characteristics of the recording section 125.

The recording signal conversion section 124 performs recording signal conversion processing of converting pieces of C, M, and Y image information into a signal suitable for the recoding device of the recording section 125. For example, in the fusion thermal transfer recording scheme, the recording signal conversion section 124 generates a driving voltage control signal, a driving pulse signal, and the like for the thermal head. The recording signal conversion section 124 also performs heat control and the like for the thermal head.

The recording section 125 performs recording processing (printing processing) for a recording medium on the basis of signals from the recording signal conversion section 124. The recording section 125 performs printing processing by, for example, the alternate driving/recording scheme. In performing printing processing by the alternate driving/recording scheme, the recording section 125 alternately forms and records, on a recording medium, even-numbered and odd-numbered pixels in the main scanning direction of a recording device typified by a thermal head on a recording line basis on the basis of signals from the recording signal conversion section 124.

In the arrangement shown in FIG. 18, after the electronic watermark embedding section 122 performs electronic watermark embedding processing, the image processing section 123 performs image processing for printing operation. In contrast to this, in the arrangement shown in FIG. 19, after the image processing section 123 performs image processing for printing operation, the electronic watermark embedding section 122 performs electronic watermark embedding processing.

In the image recording apparatus having the arrangement shown in FIG. 18, since image processing, e.g., color conversion, for printing operation, is performed after electronic watermark embedding processing, the electronic watermark embedding section 122 processes image information constituted by three fundamental colors, i.e., R, G, and B, input from the image input section 121. In contrast, in the image recording apparatus having the arrangement shown in FIG. 19, since electronic watermark embedding processing is performed after image processing, e.g., color conversion, for printing operation, the electronic watermark embedding section 122 processes image information constituted by three fundamental colors, i.e., C, M, and Y, converted by the image processing section 123.

In the image recording apparatus having the

arrangement shown in FIG. 18, image input processing
and electronic watermark embedding processing are
continuously performed. In the arrangement shown in
FIG. 18, therefore, the image input section 121 and
electronic watermark embedding section 122 can be
integrated into one image processing module. In
addition, in the image recording apparatus having the
arrangement shown in FIG. 18, image processing (color
conversion processing) for printing operation,
recording signal conversion processing, and recording
processing are continuously performed. In the
arrangement shown in FIG. 18, therefore, the image
processing section 123 for printing operation,
recording signal conversion section 124, and recording
section 125 can be integrated into one piece of
hardware such as a printer. That is, the arrangement
shown in FIG. 18 has an advantage that the arrangement
of hardware for implementing an image recording
apparatus is simple.

In contrast to this, in the image recording
apparatus having the arrangement shown in FIG. 19,
since electronic watermark embedding processing is
performed after image processing (color conversion
processing) for printing operation for an input
image, electronic watermark data is resistant to
deterioration. In general, it is preferable to
minimize image processing for a composite image in

which electronic watermark data is embedded. This is
because the electronic watermark data embedded in
the composite image may deteriorate during image
processing. Therefore, the arrangement shown in
FIG. 19 is advantageous over the arrangement shown in
FIG. 18 in that a composite image can be printed on a
recording medium without degrading the electronic
watermark data embedded in the composite image.

As described above, the recording signal
conversion processing by the recording signal
conversion section 124 must be done immediately before
the recording processing by the recording section 125.
For this reason, the order of recording signal
conversion processing cannot be changed. The apparatus
shown in FIG. 19 is therefore configured to perform
electronic watermark embedding processing immediately
before recording signal conversion processing.

FIG. 20 is a view showing the array of dots in an
image to be recorded by an image recording apparatus
having an arrangement like that shown in FIG. 18 or 19.
Referring to FIG. 20, the respective dots are arrayed
at a pitch $\underline{d}$ instead of every other dot. On a line
A - A' in FIG. 20, the respective dots are arranged at
$1/\sqrt{2}$ the pitch of the heating elements of the thermal
head instead of every other dot. In addition, the line
A - A' in FIG. 20 has an angle of 45° with the main
scanning direction.

The second embodiment will be described next.

The first embodiment described above has exemplified the case wherein rotation processing in the second pre-processing is performed at an angle of 45° to embed sub-information at an angle of 45°, as shown in FIG. 20. FIG. 20 shows the case wherein the interval between even-numbered and odd-numbered lines is equal to the pitch of the heating elements of the recording head (thermal head). In the case shown in FIG. 20, therefore, the direction in which dots are arrayed in a line has an angle of 45° with the main scanning direction (the horizontal direction in FIG. 20).

The second embodiment will exemplify a case of another rotation angle as shown in FIG. 21. In the case shown in FIG. 21, the interval between even-numbered and odd-numbered lines is set to 1/2 a pitch d of the heating elements of a recording head (thermal head). Referring to FIG. 21, the direction in which dots are arrayed in a line has an angle of about 26.565° with the main scanning direction (the horizontal direction in FIG. 21). In this case, if sub-information is embedded in main image information at an angle like that shown in FIG. 21, the embedded sub-information is not lost even by recording processing based on the alternate driving/recording scheme.

The flow of actual processing in the second embodiment will be described. FIG. 14 is a flow chart showing the flow of processing according to the second embodiment.

First of all, the image recording apparatus performs image input processing of inputting main image information (step S131). In step S131, as in step S101 in FIG. 1, facial image information as main image information is digitized and input by photographing a facial image with a camera or capturing a facial portrait with an image input device such as a scanner.

The image recording apparatus performs the first pre-processing for the main image information input by the image input processing (step S132). In the first pre-processing, the data of the main image information in the sub-scanning direction (the feeding direction of a recording medium in the image recording apparatus), which is obtained by the image input processing in step S131, is continuously arrayed in two columns to make the pixel size in the sub-scanning direction twice the original size.

The image recording apparatus then performs the second pre-processing for the main image information having undergone the first pre-processing (step S133). In the second pre-processing, thinning-out processing is performed for the main image information obtained by the first pre-processing in step S132.

The image recording apparatus performs electronic watermark embedding processing for the main image information having undergone the second pre-processing (step S134). In this electronic watermark embedding processing, sub-information (sub-image information) is embedded as electronic watermark data in the main image information (image information subjected to embedding) for which all the pre-processing has been done. With this operation, in the electronic watermark embedding processing, composite image information is created by embedding, in the image information subjected to embedding, the sub-information (sub-image information) in an invisible state such that the sub-information cannot be perceived by the human eye. Note that the electronic watermark embedding processing is the same as that in the first embodiment, and hence a detailed description thereof will be omitted.

Finally, the image recording apparatus performs recording processing of recording, on a recording medium, the composite image information created by the above electronic watermark embedding processing (step S135). That is, in this recording processing, the pitch in the sub-scanning direction is set to 1/2 the pitch d in the main scanning direction, and the composite image information created in step S134 is recorded on the recording medium serving as a personal authentication medium by the alternate

driving/recording scheme. The pitch in the
sub-scanning direction is controlled by, for example,
the convey pitch of the recording medium in the image
recording apparatus. Note that the alternate

5 driving/recording scheme is a scheme of alternately
forming even-numbered and odd-numbered pixels in the
main scanning direction of a recording device typified
by a thermal head on a recording line basis.

As described above, in the first and second
10 embodiments, the first pre-processing corresponding to
pixel formation processing for image recording is
performed for main image information. The second
pre-processing of geometric transformation is then
performed for the main image information having
15 undergone the first pre-processing. Composite image
information is created by embedding sub-information in
the main image information having undergone the second
pre-processing in an invisible state. Transformation
processing inverse to the second pre-processing is
20 performed for the created composite image information.
The resultant composite image information is recorded
on a recording medium by the alternate driving/
recording scheme.

According to the first and second embodiments,
25 therefore, an image processing method and image
recording apparatus can be provided, which can create
composite image information by embedding, in main image

information to be recorded on a recording medium such as a personal authentication medium, another additional sub-information in an invisible state, and maintain the electronic watermark data in the composite image

5 information recorded on the recording medium.

In addition, according to the first and second embodiments, an image processing method and image recording apparatus can be provided, which allow the electronic watermarking technique to be applied to a

10 to-be-recorded image while maintaining high gradation performance in an image recording apparatus based on the fusion thermal transfer recording scheme, and can maintain electronic watermark data (sub-information) so as to protect the data from destruction even when it is

15 recorded on a recording medium.

The third, fourth, and fifth embodiments will be described below with reference to the several views of the accompanying drawing.

The third embodiment will be described first.

20 FIG. 23 schematically shows the arrangement of a printed material according to the third embodiment. For example, a facial image 302, a ghost image 303, characters 304, and a predetermined graphic pattern (a star in FIG. 23) 305 are printed on a printed material

25 301 in a visible state. The facial image 302 is a human facial image formed from a color multilevel image. The ghost image 303 is a facial image obtained

by decreasing the density of the facial image 302. The
characters 304 are printed as binary images. The
graphic pattern 305 is a predetermined graphic pattern
such as a star.

5   A binary image 306 is embedded in the ghost image
303 so as to be difficult to perceive by the human eye.
The binary image 306 is created from data associated
with the image printed on the printed material 301. In
the case shown in FIG. 23, the graphic pattern (star)

10   305 is printed while being embedded as the binary image
306 in the ghost image 303.

A hologram pattern 307 serving as an optical
security pattern is formed on the image printed on the
printed material 301. In the case shown in FIG. 23,

15   patterning is performed such that the hologram pattern
307 does not exist on the facial portion of the ghost
image 303 in which the binary image 306 is embedded.

A method of printing the facial image 302 and
ghost image 303 according to the third embodiment will

20   be described next.

FIG. 24 is a flow chart for explaining printing
procedures for the facial image 302 and ghost image
303. Assume that in this case, the printed material
301 is created by an image recording apparatus having

25   an image input unit 311, control unit 312, and
printer 313.

First of all, the control unit 312 performs facial

image capturing processing of capturing a color human facial image (step S301). A color human facial image is captured from, for example, the image input unit 311 such as a scanner or digital camera. Assume that in the above facial image capturing processing, a facial image is captured as a color image formed from red (R), green (G), and blue (B) signals. The facial image 302 and ghost image 303 to be printed on the printed material 301 are created on the basis of the color facial image formed from the R, G, and B signals captured by this facial image capturing processing.

The processing of creating the facial image 302 will be described first. The facial image 302 is created by performing the processing in steps S302 to S304 in FIG. 24 for the color facial image captured by the above facial image capturing processing.

More specifically, upon capturing a color facial image formed from R, G, and B signals by the above facial image capturing processing, the control unit 312 performs color conversion processing of converting the R, G, and B signals of the color facial image into color signals for printing operation, including yellow (Y), magenta (M), and cyan (C) signals or Y, M, C, and black (K) signals (step S302). Image processing such as edge emphasis and brightness correction is performed for the facial image having undergone color conversion by the color conversion processing (step S303). The

control unit 312 also performs recording signal

conversion processing of converting the facial image

having undergone the image processing in step S303 into

a recording signal for driving the printer 313 (step

5 S304). The signal generated by this recording signal

conversion processing is output to the printer 313.

Note that the printer 313 is, for example, a

printer designed to perform printing by using the

thermal transfer recording scheme of performing thermal

10 transfer recording by using a line thermal head having

a plurality of heating elements arrayed in a line.

The ghost image 303 is processed as follows.

First of all, the control unit 312 performs reduction

processing of reducing the facial image captured from

15 the image input unit 311 in step S301 (step S305).

Upon reducing the facial image by this reduction

processing, the control unit 312 performs density

reduction processing of reducing the density of the

reduced facial image to 1/2 or less the normal density

20 (step S306). The image obtained by this density

reduction processing is the data of a ghost image

serving as a main image in which sub-information is to

be embedded.

The control unit 312 then performs electronic

25 watermark embedding processing of embedding the

binary image data of the graphic pattern 305 as

sub-information prepared in advance in the ghost image

data obtained in step S306 (step S307). This
electronic watermark embedding processing creates image
data (composite image information) by embedding the
above binary image data in the ghost image data. Color

5   conversion processing (step S302), image processing
(step S302), and recording signal conversion processing
(step S302) are executed for this composite image
information like the above facial image. As a
consequence, the ghost image in which the binary image

10   data of the graphic pattern 305 is embedded is sent as
a recording signal to the printer 313.

      Note that in the first embodiment, color
conversion processing and image processing may be
executed before electronic watermark embedding

15   processing, as described above with reference to
FIGS. 18 and 19

      Through the above processing, the facial image 302
and ghost image 303 are printed on the recording
medium. In this case, the ghost image 303 is a facial

20   image with a low density. Therefore, the ghost image
303 itself is difficult to perceive by the human eye,
and noise in the image is also difficult to perceive by
the human eye. In addition, the binary image 306
embedded in the ghost image 303 is relatively light in

25   color, and hence is difficult to perceive by the human
eye. Note that the ghost image 303 serves to prevent
tampering or copying of the printed material 301.

As described above, even if printing is performed by using a low-resolution printer, noise caused when the binary image 306 is embedded is difficult to perceive. This makes it possible to improve the security of the printed material 301. In the third embodiment, the binary image 306 is embedded in the ghost image 303. This makes tampering difficult and can improve security as compared with the case wherein only the ghost image 303 is printed.

As described above, according to the third embodiment, the facial image 302 which is a multilevel image, the ghost image 303 which is a facial image obtained by reducing the density of the facial image 302, the characters 304, and the graphic pattern 305 are printed, the ghost image 303 are printed on the printed material 301. On the printed material 301, the ghost image 303 is printed while the graphic pattern 305 printed on the printed material 301 is embedded as the binary image 306 in the ghost image 303, thereby making the image difficult to perceive by the human eye.

According to the third embodiment, therefore, a printed material and a printing method which can ensure high security can be provided.

Driving of the heating elements of the thermal head of the printer according to the present invention will be described in detail next.

The following description is based on the
assumption that the printer 313 is a printer based on
the fusion thermal transfer recording scheme.

The printer 313 based on the fusion thermal
transfer recording scheme is designed to print image
information based on the presence/absence of dots on a
recording medium. In expressing a multi-tone image,
the printer 313 based on the fusion thermal transfer
recording scheme performs density conversion by
changing the areas of dots. For this reason, the
printer 313 based on the fusion thermal transfer
recording scheme is required to accurately modulate a
dot size. In order to accurately modulate a dot size,
it is preferable to alternately drive the heating
elements of the thermal head (to be described later).
The alternate driving/recording scheme is a recording
scheme of recording transfer dots in a staggered array.

Alternate driving of the heating elements of the
thermal head is a method of alternately driving the
odd-numbered heating elements of the odd-numbered
lines and the even-numbered heating elements of the
even-numbered lines on a recording line basis. When
the heating elements of the thermal head of the printer
313 are alternately driven, dots are arrayed on the
recording medium in a staggered pattern, as shown in
FIG. 4. In this case, the main scanning direction is
the direction in which the heating elements of the

thermal head are arrayed, and the sub-scanning

direction is a direction perpendicular (intersecting)

to the main scanning direction.

FIG. 25 is a view showing heating elements 309

(309a, 309b, and 309c) of the thermal head used in

the printer 313. FIGS. 26 and 27 show temperature

distributions in the ink layer of a thermal transfer

ink ribbon which is transferred by the thermal head of

the printer 313.

FIG. 26 shows the temperature distribution in the

ink layer of the thermal transfer ink ribbon in a case

wherein the respective heating elements 309 in FIG. 25

are simultaneously driven. When all the heating

elements 309 are simultaneously driven instead of being

alternately driven, the distance between the heating

elements 309 that are simultaneously driven becomes

small. For this reason, as indicated by solid lines a

in FIG. 26, heat from the respective heating elements

309 causes thermal interference, so that the

temperature distribution is flattened. With the

temperature distribution shown in FIG. 26, there is no

temperature contrast between the adjacent heating

elements 309. When, therefore, the adjacent heating

elements 309 are simultaneously driven, the printer 313

cannot perform accurate dot size modulation, resulting

in difficulty in multi-tone recording.

FIG. 27 shows the temperature distribution in the

ink layer of the thermal transfer ink ribbon in a case

wherein the respective heating elements 309 in FIG. 25

are alternately driven. As shown in FIG. 27, in the

alternate driving operation in which the adjacent

5   heating elements 309 are not simultaneously driven (the

adjacent heating elements 309 on each recording line

are not driven), the distance between the heating

elements 309 that are driven can be set to be large.

In alternate driving operation, the distance between

10   the heating elements 309 that are driven becomes twice

the interval (pitch) between the respective heating

elements 309. In this case, in the thermal head, heat

escapes to the heating elements 309 that are not

driven. As a consequence, heat interference hardly

15   occurs. In alternate driving operation, therefore, as

indicated by solid lines b in FIG. 27, the temperature

distribution in the ink layer of the thermal transfer

ink ribbon becomes steep, and a temperature contrast

can be produced between the adjacent heating

20   elements 309.

As described above, when the heating elements 309

are alternately driven, dots can be reliably formed,

and the dot size can be accurately modulated without

being influenced by adjacent dots. Alternate driving

25   of the heating elements 309 allows even the printer 313

based on the fusion thermal transfer recording scheme

to perform multi-tone recording using area gradation.

It is preferable that a multilevel image be printed by alternately driving heating elements, and a binary image be printed without performing alternate driving of the heat elements. Assume that multilevel

5   image such as the facial image 302 and ghost image 303 on the printed material 301 shown in FIG. 23 are to be printed. In this case, the printer 313 performs gradation recording by alternately driving the heating elements 309. When binary images such as the

10 characters 304 and graphic pattern 305 on the facial image 302 in FIG. 23 are to be printed, the printer 313 prints dots in lines in both the main scanning direction and the sub-scanning direction without performing alternate driving of the heat elements.

15 When printing is to be performed by alternately driving the heating elements 309, processing of rearranging pixel data in a staggered array is added to the image processing in step S303.

When the binary image 306 is embedded in the ghost

20 image 303 by alternately driving the heating elements 309, the information of every other pixel of the embedded binary image 306 is lost. This is because, for example, the odd-numbered dots of each even-numbered line (or the even-numbered dots of each

25 odd-numbered line) are not present. However, since the binary image 306 embedded in the ghost image is a graphic pattern or the like, when the binary image is

restored, its shape can be ensured. This therefore

allows authenticity determination using the restored

binary image 306. In addition, since the binary image

is embedded in the ghost image 303, the security of the

5   printed material 301 can be improved for the same

reason as described above.

The fourth embodiment will be described next.

FIG. 28 schematically shows printed material 401

according to the fourth embodiment. A facial image

10   302, ghost image 303, characters 304, graphic pattern

305, and hologram pattern 307 are printed on the

printed material 401 like the printed material 301 in

FIG. 23. Since the facial image 302, characters 304,

graphic pattern 305, and hologram pattern 307 are

15   identical to those on the printed material 301 in

FIG. 23, a description thereof will be omitted. The

printed material 401 shown in FIG. 28 differs from the

characters 304 shown in FIG. 23 in that a binary image

406 is embedded in the ghost image 303 at a certain

20   angle. FIG. 29 shows, for example, a case wherein the

binary image 406 is embedded at an angle of 45°.

As described above, in the fusion thermal transfer

recording scheme, a multilevel image is recorded by

the alternate driving/recording scheme to express

25   gradation. Therefore, a dot array like that shown in

FIG. 20 or 21 is obtained. As described above, FIG. 20

shows the case wherein the interval d between an

even-numbered line and an odd-numbered line is equal to the pitch $\underline{d}$ of the heating elements of the thermal head. In the case shown in FIG. 20, the direction in which dots are arrayed in a line is 45° with respect to the main scanning direction (the horizontal direction in FIG. 20). FIG. 21 shows the case wherein the interval between an even-numbered line and an odd-numbered line is 1/2 the pitch of the heating elements of the thermal head. In the case shown in FIG. 21, the direction in which dots are arrayed in a line is about 26.565° with respect to the main scanning direction (the horizontal direction in FIG. 21).

If, therefore, the binary image 406 is embedded in the ghost image 303 at the above angle, the pixel data of the embedded binary image 406 is not lost even when alternate driving operation is performed.

FIG. 29 is a flow chart for explaining a processing sequence according to the fourth embodiment. The flow chart of FIG. 29 is a flow chart for explaining a sequence for printing processing of the facial image 302 and ghost image 303 in FIG. 28.

Printing processing of the facial image 302 is performed by the same sequence as that for the processing in FIG. 24 (steps S301 to S304). Assume that the processing of rearranging the pixel data of only a facial image in a staggered array is added to the image processing in step S303 as the printing

processing of the facial image 302.

In the printing processing of the ghost image 303, multilevel error diffusion processing (step S408) is added to the processing in steps S301 to S307 in FIG. 24. That is, as shown in FIG. 29, the printing processing of the ghost image 303 is performed by sequentially executing facial image capturing processing (step S301), reduction processing (step S305), density reduction processing (step S306), electronic watermark embedding processing (step S307), color conversion processing (step S302), image processing (step S303), multilevel error diffusion processing (step S408), and recording signal conversion processing (step S304).

The multilevel error diffusion processing (step S408) shown in FIG. 29 is performed for the image data of the ghost image 303 having undergone the image processing in step S303. The recording signal conversion processing (step S304) is performed for the ghost image 303 having undergone the multilevel error diffusion processing in step S408.

Note that in the printing processing of the ghost image 303, the facial image capturing processing (step S301), reduction processing (step S305), density reduction processing (step S306), electronic watermark embedding processing (step S307), color conversion processing (step S302), and image processing (step

S303) are the same as those (steps S301 to S307) in FIG. 24. In the electronic watermark embedding processing in step S307, to-be-embedded binary image data is embedded in the ghost image data at a certain angle.

A specific example of the multilevel error diffusion processing in step S408 in FIG. 29 will be described next. A case wherein the error diffusion processing is quaternary, i.e., quaternary error diffusion processing, will be described below.

Assume that in this example of quaternary error diffusion processing, the quantization resolution is set to 0 to 255. Assume also that multilevel quantization levels, i.e., set density values, are 0, 85, 170, and 255, and multilevel thresholds are 50, 128, and 210. In addition assume that with respect to a target pixel, a position a (adjacent to the target pixel in the main scanning direction) is diffused to 9/16; a position b (below the target pixel in the sub-scanning direction, to 4/16; and a position c, to 3/16.

Although quaternary error diffusion processing will be described below with the above thresholds and quantization levels, the respective values (the parameter values for multilevel error diffusion processing) may be set to other values. In addition, the quantization resolution may be set to values other

than 0 to 255.

In the above multilevel error diffusion processing, multilevel quantization processing and error diffusion processing are performed on the basis of the above parameter values. In the multilevel error diffusion processing, target pixels are sequentially input in the main scanning direction (raster scan), and multilevel quantization processing and error diffusion processing are performed for each pixel. When multilevel error diffusion processing for one line is completed, multilevel error diffusion processing for the next line in the sub-scanning direction is performed. With this operation, the target pixels of each line are sequentially input in the main scanning direction to perform multilevel error diffusion processing.

That is, in multilevel error diffusion processing, target pixels are sequentially input in the main scanning direction, and multilevel quantization processing is performed on the basis of the above parameter values. The quantization errors produced during multilevel quantization processing are multiplied by diffusion coefficients in error diffusion processing. As a consequence, the quantization errors produced during the multilevel quantization processing are diffused to neighboring image regions for which no multilevel quantization processing has been performed.

Quaternary error diffusion processing will be described next with reference to an example of an image (four pixels) like the one shown in FIG. 31.

In step S411 shown in FIG. 31, the respective input data values corresponding to four pixels for one line in the main scanning direction are shown. Assume that each of the input data values of the four pixels shown in step S411 in FIG. 31 is "43" which is about half of the quantization level value "85".

First of all, in quantization processing for the first pixel, the input data value of the first pixel is compared with the threshold. In this case, the input data value ("43") of the first pixel is equal to or more than "0" and less than "50". The quantization level value of the first pixel is converted into "0". In this case, the quantization error is "43 - 0 = 43".

When a quantization error is calculated by the above quantization processing, error diffusion processing is performed on the basis of the above quantization error. In error diffusion processing for the first pixel, the value of the quantization error ("43") is multiplied by the diffusion coefficient shown in FIG. 30 for a neighboring pixel. By this error diffusion processing, the quantization error corresponding to the first pixel is diffused to the neighboring pixel. As a result, as indicated by step S412 in FIG. 31, the data value of the second pixel

becomes "59" obtained by adding the diffusion error
to "43".

Similar to the processing for the first pixel, the
second pixel is subjected to multilevel quantization
5   processing. As a result of this processing, the
quantization error is diffused to a neighboring pixel.
As a result, as indicated by step S413 in FIG. 31, the
quantization level value of the second pixel is
converted into "85". The quantization error in the
10   multilevel quantization processing for the second pixel
becomes "59 - 85 = -26", and the data value of the
third pixel becomes "24".

The third pixel is subjected to multilevel
quantization processing in the same manner. As a
15   result of this processing, the quantization error is
diffused to a neighboring pixel. As a consequence, as
indicated by step S414 in FIG. 31, the quantization
level value of the third pixel is converted into "0",
and the data value of the fourth pixel becomes "56".
20   The fourth pixel is subjected to multilevel
quantization processing in the same manner. As a
result of this processing, the quantization error is
diffused to a neighboring pixel. As a consequence, as
indicated by step S415 in FIG. 31, the quantization
25   level value of the fourth pixel is converted into "85".

The data value of each pixel shown in step S415 in
FIG. 31 is the final processing result of quaternary

error diffusion processing for each pixel in step S411.
Therefore, the data values of a group of pixels each
having pixel data 1/2 the quantization level value "85"
(four pixels each having an input data value of "43")
5   are alternately converted into "85".

That is, when the first and second pixels are
viewed macroscopically, the density of the corre-
sponding portion looks about "43", which is almost half
of "85". When multilevel error diffusion processing is
10   performed, the gradation of an image viewed as a
macro-area is maintained, and hence an image conforming
to the input image can be obtained.

In the above multilevel error diffusion
processing, target pixels are sequentially input in
15   the main scanning direction, and neighboring pixels
subjected to error diffusion are pixels around each
target pixel (there is no gap corresponding to even one
pixel).

In this case, each pixel data (image data for
20   printing operation in the alternate driving scheme) for
recording an image by using the alternate driving
scheme for the heating elements must be set such that
each adjacent pixel in the main scanning direction has
"0" data. In image data for printing operation based
25   on the alternate driving scheme, therefore, each pixel
to which an error should be diffused is not located
adjacent to a corresponding target pixel.

In addition, in image data for printing operation based on the alternate driving scheme, the nearest adjacent pixel to each target pixel is a lower oblique pixel with respect to the target pixel. That is, in

5   image data for printing operation based on the alternate driving scheme, a pixel to which an error should be diffused most is not the next pixel to the target pixel in the main scanning direction. For this reason, if general error diffusion processing is

10   performed for image data for printing operation based on the alternate driving scheme, a quantization error is not properly diffused in a printer based on the alternate driving scheme. As a consequence, the gradation of an image regarded as a macro-area may not

15   be maintained.

In the fourth embodiment, therefore, the multilevel error diffusion processing shown in FIG. 29 is performed by a processing sequence like that shown by the flow chart of FIG. 32. First of all, in the

20   multilevel error diffusion processing (step S408) shown in FIG. 29, image data is input as original image data through the image processing in step S303 in FIG. 29 (step S420). This original image data is formed from monochrome pixel data decomposed into Y, M, and C

25   components or Y, M, C, and K components. After desired data processing is performed for the input original image, the pixel data of the original image are

rearranged in a staggered array (step S421).

The respective pixels arranged in the staggered array are rearranged in a line in the main scanning direction and sub-scanning direction (step S422). Multilevel quantization processing and error diffusion processing like those described above are performed for the respective pixels rearranged in a line (step S423). Finally, the pixels having undergone the multilevel quantization processing and error diffusion processing are rearranged in the original staggered array (step S424).

By performing such multilevel error diffusion processing, a quantization error corresponding to each pixel can be diffused to the nearest adjacent pixel. This eliminates the necessity to prepare any special error diffusion coefficient. That is, in the above multilevel error diffusion processing, multilevel quantization processing and multilevel error diffusion processing can be easily performed for only pixels to be actually recorded by the alternate driving scheme.

As described above, when multilevel error diffusion processing is performed for the ghost image 303, the respective dots corresponding to pixel data for printing operation are printed in a properly dispersed state. For this reason, the dots of the binary image 306 embedded in the ghost image 303 are also dispersed. When, therefore, the dots

corresponding to the pixel data for printing operation

are dispersed, some dots of the binary image 306

embedded in the ghost image 303 are lost. If, however,

multilevel error diffusion processing, since the

5   density of the image is maintained from a macroscopic

viewpoint, the shape of the embedded binary image 306

is held.

When the dots of the binary image 306 are properly

dispersed, the binary image 306 embedded in the ghost

10   image 303 becomes difficult to perceive by the human

eye. This is because the human eye perceives a given

image upon averaging the densities of neighboring

images. According to the fourth embodiment, therefore,

the binary image 306 embedded in the ghost image 303

15   can be made difficult to perceive, and hence the

security of the printed material 301 can be improved.

The fifth embodiment will be described next.

FIG. 33 is a flow chart showing a processing

sequence according to the fifth embodiment. The flow

20   chart of FIG. 33 shows a printing sequence for a facial

image 302 and ghost image 303 according to the fifth

embodiment.

Printing processing of the facial image 302 is

performed by the same sequence as that for the

25   processing in FIG. 24 (steps S301 to S304). Assume

that the image processing in step S303 as the printing

processing of the facial image 302 additionally

includes the processing of rearranging the pixel data of only a facial image in a staggered array.

The printing processing of the ghost image 303 is equivalent to the processing in steps S301 to S307 in FIG. 24 to which binary error diffusion processing (step S509) is added. That is, as shown in FIG. 29, the printing processing of the ghost image 303 is performed by sequentially executing facial image capturing processing (step S301), reduction processing (step S305), density reduction processing (step S306), electronic watermark embedding processing (step S307), color conversion processing (step S302), image processing (step S303), binary error diffusion processing (step S509), and recording signal conversion processing (step S304).

The binary error diffusion processing (step S209) shown in FIG. 29 is performed for the image data of the ghost image 303 having undergone the image processing in step S303 described above. The above recording signal conversion processing (step S304) is performed for the ghost image 303 having undergone the binary error diffusion processing in step S509 described above.

In the printing processing of the ghost image 303, the above facial image capturing processing (step S301), reduction processing (step S305), density reduction processing (step S306), electronic watermark

embedding processing (step S307), color conversion

processing (step S302), and image processing (step

S303) are the same as those shown in FIG. 24 (steps

S301 to S307). In the electronic watermark embedding

5   processing in step S307, to-be-embedded binary image

data is embedded in ghost image data without being

inclined. In addition, the pixels of the ghost image

are not rearranged in a staggered array.

In the binary error diffusion processing in step

10   S509, the processing described with reference to

FIGS. 30 and 31 is performed. For example, the

quantization level is set to only "255", and a

threshold of "127" is selected. Alternatively,

thresholds may be determined by random numbers to

15   disperse pixels more properly and make it difficult

to produce noise such as a texture. Note that

quantization processing is not limited to error

diffusion processing. For example, other kinds of

quantization processing such as dither processing may

20   be used.

If binary error diffusion processing is performed

as in the fifth embodiment described above, dots as

pixels for printing operation need not be arranged in a

staggered array. According to the fifth embodiment,

25   therefore, the ratio of pixel data lost to all the

pixel data of an embedded binary image 306 can be

reduced. In the fifth embodiment, since there is no

need to array dots as pixels for printing operation in a staggered array, it is not necessary to perform the processing of inclining the to-be-embedded binary image 306. In addition, according to the fifth embodiment,

5 performing binary error diffusion makes it possible to properly disperse dots and makes it difficult to perceive the embedded binary image 306 by the human eye. Therefore, the security of the printed material 301 can be improved.

10 When the authenticity of the printed material 301 created by using the third, fourth, and fifth embodiments is to be determined, the ghost image 303 is read by a scanner or the like. The embedded binary image 306 is then restored from the read image data, and its

15 authenticity is determined. When a hologram pattern 307 is present in the portion where the binary image 306 is embedded, the hologram pattern 307 is read together. This makes it necessary to remove the influence of the hologram pattern by applying a special

20 filter.

In the third, fourth, and fifth embodiments, however, as shown in FIGS. 23 or 28, protective layer is formed to prevent the hologram pattern 307 from being formed in the portion where the binary image 306

25 of the ghost image 303 is embedded. When authenticity determination is to be performed, therefore, the influence of the hologram pattern 307 can be

eliminated, and there is no need to perform extra processing.

The third, fourth, and fifth embodiments have exemplified the case wherein a facial image is a color multilevel image. However, the present invention is not limited to this. For example, a facial image may be a monochrome image. In addition, the present invention can be applied to a printed material on which a monochrome multilevel image such as a sign is printed.

As has been described in detail above, according to the third, fourth, and fifth embodiments, a printed material having high security and a printing method which is used to create a printed material having high security can be provided.